

## Wearcoat 800 Crack Filler Part A

<b>1</b>	<b>PRODUCT AND COMPANY IDENTIFICATION</b>
----------	-------------------------------------------

**Product Identifier:** Wearcoat 800 Crack Filler Part A  
**Common Name:** Epoxy Resin Compound  
**SDS Number:** I63  
**Revision Date:** 8/19/2015  
**Version:** 1  
**Chemical Family:** Epoxy Resin  
**Instructions:** Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.  
**Supplier Details:** Coatings for Industry, Inc.  
 319 Township Line Road  
 Souderton, PA 18964  
**Emergency:** Infotrac  
**Contact:** USA: 1-800-535-5053 / International :352-323-3500  
**Phone:** 215-723-0919  
**Fax:** 215-723-0911  
**Email:** cs@cficoatings.com  
**Web:** www.cficoatings.com

<b>2</b>	<b>HAZARDS IDENTIFICATION</b>
----------	-------------------------------

### Classification of the substance or mixture

**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):**

- Health, Respiratory or skin sensitization, 1 Skin
- Health, Skin corrosion/irritation, 2
- Health, Carcinogenicity, 2
- Health, Specific target organ toxicity - Repeated exposure, 2
- Health, Serious Eye Damage/Eye Irritation, 2 A
- Environmental, Hazards to the aquatic environment - Chronic, 2

### GHS Label elements, including precautionary statements

**GHS Signal Word:** **WARNING**

**GHS Hazard Pictograms:**



**GHS Hazard Statements:**

- H317 - May cause an allergic skin reaction
- H315 - Causes skin irritation
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure
- H319 - Causes serious eye irritation
- H411 - Toxic to aquatic life with long lasting effects

**GHS Precautionary Statements:**

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/protective clothing

## Wearcoat 800 Crack Filler Part A

P302+352 - IF ON SKIN: Wash with soap and water.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P308+313 - IF exposed or concerned: Get medical advice/attention.

P332+313 - If skin irritation occurs: Get medical advice/attention.

P337 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P401 - Store away from incompatible materials.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 COMPOSITION/INFORMATION OF INGREDIENTS

#### Ingredients:

Cas#	%	Chemical Name
25068-38-6	30-60%	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
1317-65-3	10-30%	Calcium carbonate
14807-96-6	5-15%	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )
14228-73-0	1-5%	Oxirane, 2,2'-[1,4-cyclohexanediylbis(methyleneoxymethylene)]bis-
112945-52-5	1-5%	Silicon Dioxide, Chemically Prepared
1333-86-4	0.1-1%	Carbon black
14808-60-7	0.1-1%	Quartz (SiO <sub>2</sub> )

Other components below reportable levels: 1-5%

### 4 FIRST AID MEASURES

**Inhalation:** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin Contact:** Remove contaminated clothing immediately and wash skin with soap and water. Remove contaminated clothing. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Then remove contact lenses, if easily removeable, and continue irrigation for not less than 15 minutes. Get medical Attention if irritation develops and persists.

**Ingestion:** Rinse mouth. Get medical advice/attention if you feel unwell.

#### Most important symptoms/effects, acute and delayed

Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

#### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5 FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Wearcoat 800 Crack Filler Part A

**Specific hazards arising from the chemical**

During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire-fighting equipment/instructions**

Use water spray to cool unopened containers.

**Specific methods**

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**

No unusual fire or explosion hazards noted.

<b>6</b>	<b>ACCIDENTAL RELEASE MEASURES</b>
----------	------------------------------------

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Stop the flow of material, if this is without risk. Collect spillage. Dike far ahead of spill for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

<b>7</b>	<b>HANDLING AND STORAGE</b>
----------	-----------------------------

**Handling Precautions:**

Provide appropriate exhaust ventilation at places where dust is formed. Keep formation of airborne dusts to a minimum. Do not breathe dust. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash contaminated clothing before reuse. Avoid release to the environment. Do not empty into drains.

**Storage Requirements:**

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

<b>8</b>	<b>EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
----------	----------------------------------------------

**Engineering Controls:**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Personal Protective Equipment:**

Eye/face protection  
Wear safety glasses with side shields (or goggles).

Hand protection  
Wear appropriate chemical resistant gloves.

Skin protection  
Wear appropriate chemical resistant clothing.

**Wearcoat 800 Crack Filler Part A**

Respiratory protection

Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [30-60%] : no data available**

**Calcium Carbonate (CAS 1317-65-3) [10-30%]**

PEL 5 mg/m3 Respirable fraction. US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)  
 15 mg/m3 Total dust.

**Talc (Mg3H2(SiO3)4) (14807-96-6) [5-15%]**

Components with workplace control parameters

TWA 20Million USA. Occupational Exposure Limits (OSHA) - Table Z-3  
 particles per cubic foot Mineral Dusts

Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Containing less than 1% quartz; if 1% quartz or more, use quartz limit. mppcf X 35.3 = million particles per cubic meter = particles per c.c

TWA 2 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants -1910.1000

TWA 2 mg/m3 USA. NIOSH Recommended Exposure Limits

TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  
 Lower Respiratory Tract irritation The value is for particulate matter containing no asbestos and < 1% crystalline silica Not classifiable as a human carcinogen

**Oxirane, 2,2'-[1,4-cyclohexanediylbis(methyleneoxymethylene)]bis- (14228-73-0) [1-5%] : no data available**

**Carbon black (1333-86-4) [0.1-1%]**

Components with workplace control parameters

TWA 3.5 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  
 Not classifiable as a human carcinogen

TWA 3.5 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

TWA 3.5 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

TWA 3.5 mg/m3 USA. NIOSH Recommended Exposure Limits

TWA 0.1 mg/m3 USA. NIOSH Recommended Exposure Limits  
 Potential Occupational Carcinogen  
 Carbon black in presence of polycyclic aromatic hydrocarbons(PAHs)

## Wearcoat 800 Crack Filler Part A

**Quartz (SiO<sub>2</sub>) (14808-60-7) [0.1-1%]**

Components with workplace control parameters

TWA 0.025 mg/m<sup>3</sup> USA. ACGIH Threshold Limit Values (TLV)  
Suspected human carcinogen

TWA 0.025 mg/m<sup>3</sup> USA. ACGIH Threshold Limit Values (TLV)  
Lung cancer Pulmonary fibrosis Suspected human carcinogen

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational Exposure Limits are not relevant to the current physical form of the product.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Blue	<b>Odor:</b>	Slight
<b>Physical State:</b>	Paste	<b>Flash Point:</b>	> 400.0 °F (> 204.4 °C) Pensky-Martens
<b>Spec Grav./Density:</b>	12.08 lb/gal	<b>Vapor Density:</b>	> 1
<b>Boiling Point:</b>	> 500 °F (> 260 °C)	<b>VOC:</b>	0 g/l
<b>Vapor Pressure:</b>	0.03 mm Hg		
<b>Evap. Rate:</b>	< 1 BuAc		

**10 STABILITY AND REACTIVITY**

<b>Reactivity:</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical Stability:</b>	Product is stable under normal conditions.
<b>Conditions to Avoid:</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Materials to Avoid:</b>	Strong Oxidizing Agents.
<b>Hazardous Decomposition:</b>	No hazardous decomposition products are known.
<b>Hazardous Polymerization:</b>	Will not occur.

**11 TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

**Ingestion** Expected to be a low ingestion hazard.

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

**Information on toxicological effects**

**Acute toxicity** Harmful in contact with skin. May cause an allergic skin reaction.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not available.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

## Wearcoat 800 Crack Filler Part A

**Carcinogenicity** In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged exposure.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.  
Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.  
Silicon Dioxide (CAS 112945-52-5) 3 Not classifiable as to carcinogenicity to humans.  
Talc (CAS 14807-96-6) 2B Possibly carcinogenic to humans.  
3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Chronic effects** Prolonged exposure may cause chronic effects.

**Information on individual components:****Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [30-60%]**

Information on toxicological effects

Acute toxicity:

Oral LD50 Oral - rat - 13,600 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Lungs, Thorax, or Respiration:Dyspnea. Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

Inhalation LC50 no data available

Dermal LD50 no data available

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: May cause sensitization by skin contact.

Germ cell mutagenicity: no data available

Genotoxicity in vitro - Ames test - positive

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

---

## Wearcoat 800 Crack Filler Part A

---

Teratogenicity: no data available  
Specific target organ toxicity - single exposure (Globally Harmonized System): no data available  
Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available  
Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.  
Synergistic effects: no data available

Additional Information:

RTECS: KC2100000

### Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) (14807-96-6) [5-15%]

Information on toxicological effects

Acute toxicity:

Oral LD50 no data available  
Inhalation LC50 no data available  
Dermal LD50 no data available

Other information on acute toxicity

Skin corrosion/irritation: Skin - Human - Mild skin irritation - 3 h  
Serious eye damage/eye irritation: no data available  
Respiratory or skin sensitization: no data available  
Germ cell mutagenicity: no data available

Carcinogenicity:

Carcinogenicity - rat - Inhalation:

Tumorigenic:Carcinogenic by RTECS criteria. Lungs, Thorax, or Respiration:Bronchiogenic carcinoma. Endocrine:Tumors.

Carcinogenicity - rat - Inhalation:

Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Lungs, Thorax, or Respiration:Tumors.

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 1 - Group 1: Carcinogenic to humans (Quartz)

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Hydrous magnesium silicate)

NTP: Known to be human carcinogen (Quartz)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): Inhalation - May cause respiratory irritation. - Lungs  
Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation Toxic if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP.

Synergistic effects: no data available

Additional Information:

---

## Wearcoat 800 Crack Filler Part A

---

RTECS: WW2710000

### **Oxirane, 2,2'-[1,4-cyclohexanediy]bis(methyleneoxymethylene)]bis- (14228-73-0) [1-5%]**

#### Information on toxicological effects

##### Acute toxicity:

Oral LD50 no data available  
Inhalation LC50 no data available  
Dermal LD50 no data available

##### Other information on acute toxicity

Skin corrosion/irritation: no data available  
Serious eye damage/eye irritation: no data available  
Respiratory or skin sensitization: May cause allergic skin reaction.  
Germ cell mutagenicity: no data available

##### Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.  
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.  
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: Not available

### **Carbon black (1333-86-4) [0.1-1%]**

#### Information on toxicological effects

##### Acute toxicity:

LD50 Oral - rat - male and female - > 8,000 mg/kg (OECD Test Guideline 401)  
Inhalation: no data available  
LD50 Dermal - rabbit - > 3,000 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: No skin irritation - 24 h (OECD Test Guideline 404)

Serious eye damage/eye irritation: Eyes - rabbit Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitisation: - guinea pig Result: Did not cause sensitisation on laboratory animals. (OECD Test Guideline 406)



---

## Wearcoat 800 Crack Filler Part A

---

Germ cell mutagenicity: Ames test S. typhimurium Result: negative  
Hamster ovary  
DNA repair rat - female

**Carcinogenicity:**

Carcinogenicity - rat - Inhalation:

Tumorigenic: Carcinogenic by RTECS criteria. Lungs, Thorax, or Respiration: Tumors.

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Carbon black)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

**Additional Information:**

RTECS: FF5800000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

**Quartz (SiO<sub>2</sub>) (14808-60-7) [0.1-1%]**

**Information on toxicological effects**

**Acute toxicity:**

Oral LD50 no data available

Inhalation LC50 no data available

Dermal LD50 no data available

**Other information on acute toxicity**

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

**Carcinogenicity:**

Limited evidence of carcinogenicity in human studies

IARC: 1 - Group 1: Carcinogenic to humans (Quartz)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Known to be human carcinogen (Quartz)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):

Inhalation - May cause damage to organs through prolonged or repeated exposure.

## Wearcoat 800 Crack Filler Part A

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity. Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential.

Synergistic effects: no data available

Additional Information:

RTECS: VV7330000

12

## ECOLOGICAL INFORMATION

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

**Persistence and degradability** Not available.

**Bioaccumulative potential** Not available.

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13

## DISPOSAL CONSIDERATIONS

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## Wearcoat 800 Crack Filler Part A

<b>14</b>	<b>TRANSPORT INFORMATION</b>
-----------	------------------------------

UN3077, Environmentally hazardous substances, solid, n.o.s., 9, PGIII

**IATA UN number** UN3077

**UN proper shipping name** Environmentally hazardous substance, solid, n.o.s. (Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

**Transport hazard class(es)**

**Class** 9

**Packing group** III

**Environmental hazards** Yes

**ERG Code** 9L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Passenger and cargo aircraft** Allowed.

**Other information**

**Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN3077

**UN proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT

**Transport hazard class(es)**

**Class** 9

**Subsidiary risk -**

**Packing group** III

**Environmental hazards**

**Marine pollutant** Yes

**EmS** F-A, S-F

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

<b>15</b>	<b>REGULATORY INFORMATION</b>
-----------	-------------------------------

Component (CAS#) [%] - CODES

-----  
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [30-60%] TSCA

Calcium carbonate (1317-65-3) [10-30%] MASS, OSHAWAC, PA, TSCA, TXAIR

Talc (Mg3H2(SiO3)4) (14807-96-6) [5-15%] MASS, OSHAWAC, PA, TSCA, TXAIR

Oxirane, 2,2'-[1,4-cyclohexanediy]bis(methyleneoxymethylene)]bis- (14228-73-0) [1-5%] TSCA

Silicon Dioxide, Chemically Prepared (112945-52-5) [1-5%] TSCA

Carbon black (1333-86-4) [0.1-1%] MASS, OSHAWAC, PA, TSCA, TXAIR

Quartz (SiO2) (14808-60-7) [0.1-1%] MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

-----  
TSCA = Toxic Substances Control Act  
MASS = MA Massachusetts Hazardous Substances List  
OSHA = OSHA workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
NRC = Nationally Recognized Carcinogens

---

## Wearcoat 800 Crack Filler Part A

---

16

### OTHER INFORMATION

**NOTICE:** This information is presented in good faith and believed to be accurate as of the effective date below. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Coatings For Industry, Inc. assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material. Regulatory requirements are subject to change and may differ from one location to another: it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The preceding specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations.